

# Stainless steel cold-drawn bars

## Trafilati in acciaio inossidabile



BRIGHT ROUND BARS EN 10088-3 Trafilati tondi EN 10088-3				weight kg/m
diameter mm	1.4305 (A303)	1.4301 (A304) 1.4307 (A304L)	1.4404 (A316L)	1.4104 (A430F)
5	0,154	0,154	0,154	0,154
6	0,222	0,222	0,222	0,222
7	0,302	0,302	0,302	0,302
8	0,395	0,395	0,395	0,395
9	0,499	0,499	0,499	0,499
10	0,617	0,617	0,617	0,617
11	0,746	0,746	0,746	0,746
12	0,888	0,888	0,888	0,888
13	1,042	1,042	1,042	1,042
14	1,208	1,208	1,208	1,208
15	1,387	1,387	1,387	1,387
16	1,578	1,578	1,578	1,578
17	1,782	1,782	1,782	1,782
18	1,998	1,998	1,998	1,998
19	2,226	2,226	2,226	2,226
20	2,466	2,466	2,466	2,466
21	2,719	2,719	2,719	2,719
22	2,984	2,984	2,984	2,984
23	3,261	3,261	3,261	3,261
24	3,551	3,551	3,551	3,551
25	3,853	3,853	3,853	3,853
26	4,168	4,168	4,168	4,168
27	4,494	4,494	4,494	4,494
28	4,834	4,834	4,834	4,834
30	5,549	5,549	5,549	5,549
32	6,313	6,313	6,313	6,313
34	7,127	7,127	7,127	7,127
35	7,552	7,552	7,552	7,552
36	7,990	7,990	7,990	7,990
38	8,903	8,903	8,903	8,903
40	9,864	9,864	9,864	9,864
42	10,875	10,875	10,875	10,875
45	12,485	12,485	12,485	12,485
50	15,413	15,413	15,413	15,413
55	18,650	18,650	18,650	18,650
60	22,195	22,195	22,195	22,195
65	26,048	26,048	26,048	26,048
70	30,209	30,209	30,209	30,209
75	34,679	34,679	34,679	34,679
80	39,457	39,457	39,457	39,457
85	44,544	44,544	44,544	44,544
90	49,938	49,938	49,938	49,938
100	61,652	61,652	61,652	61,652

BRIGHT ROUND BARS ASTM A 276 / A 479 / A 582 Trafilati tondi sec. ASTM A 276 / A 479 / A 582				weight kg/m
diameter mm - inches	1.4305 (A303)	1.4301 (A304) 1.4307 (A304L)	1.4404 (A316L)	
6,35 - 1/4"	0,249	0,249	0,249	0,249
7,937 - 5/16"	0,388	0,388	0,388	0,388
9,525 - 3/8"	0,559	0,559	0,559	0,559
11,112 - 7/16"	0,761	0,761	0,761	0,761
12,7 - 1/2"	0,994	0,994	0,994	0,994
14,287 - 9/16"	1,258	1,258	1,258	1,258
15,875 - 5/8"	1,554	1,554	1,554	1,554
17,462 - 11/16"	1,880	1,880	1,880	1,880
19,05 - 3/4"	2,237	2,237	2,237	2,237
22,225 - 7/8"	3,045	3,045	3,045	3,045
25,4 - 1"	3,978	3,978	3,978	3,978

HOT ROLLED ROUND BARS EN 10088-3, tol. k13 Tondi laminati a caldo EN 10088-3, toll. k13			weight kg/m
diameter mm	1.4301 (A304) 1.4307 (A304L)	1.4404 (A316L)	
100	61,652	61,652	61,652
110	74,599	74,599	74,599
115	81,535	81,535	81,535
120	88,779	88,779	88,779
125	96,331	96,331	96,331
130	104,192	104,192	104,192
140	120,838	120,838	120,838
150	138,717	138,717	138,717
160	157,829	157,829	157,829
170	178,174	178,174	178,174
180	199,752	199,752	199,752
190	222,563	222,563	222,563
200	246,608	246,608	246,608

Standard delivery program - Programma di fornitura standard

Dimensional tolerance - Tolleranza dimensionale k13