

Carbon steel cold-drawn bars

Trafilati in acciaio al carbonio

COLD DRAWN ROUNDS - Trafilati tondi
S235JRC, S355J2C, E335GC+S, C15, C35, C40, C45, C45S acc. to EN 10277-2
080A15 acc. to BS 970
C10R, C15R acc. to EN 10277-4
C15E, C35E, C35R, C40E, C40R, C45E, C45R, CK45 acc. to EN 10277-5

diameter mm	weight kg/m	diameter mm	weight kg/m
3	0,055	36	7,99
4	0,098	38	8,90
5	0,154	40	9,86
6	0,222	42	10,91
7	0,302	44	11,83
8	0,395	45	12,50
9	0,499	46	12,93
10	0,617	48	14,20
11	0,764	50	15,40
12	0,888	52	16,70
13	1,04	55	18,70
14	1,21	56	19,30
15	1,39	58	20,70
16	1,58	60	22,20
17	1,78	62	23,69
18	2,00	65	26,00
19	2,23	70	30,20
20	2,47	75	34,70
21	2,72	80	39,50
22	2,98	85	44,55
23	3,26	90	49,94
24	3,55	95	55,64
25	3,85	100	61,55
26	4,17	105	67,97
27	4,49	110	74,60
28	4,83	115	81,54
29	5,14	120	88,78
30	5,55	125	96,33
32	6,31	130	104,20
33	6,71	140	120,84
34	7,06	150	138,72
35	7,55	160	157,83

COLD DRAWN ROUNDS
16MnCr55 acc. to EN 10277-4
 Trafilati tondi
 16MnCr55 sec. EN 10277-4

diameter mm	weight kg/m	diameter mm	weight kg/m
10	0,617	35	7,55
11	0,764	36	7,99
12	0,888	38	8,90
13	1,04	40	9,86
14	1,21	42	10,91
15	1,39	44	11,83
16	1,58	45	12,50
17	1,78	46	12,93
18	2,00	48	14,20
19	2,23	50	15,40
20	2,47	52	16,70
21	2,72	55	18,70
22	2,98	56	19,30
23	3,26	58	20,70
24	3,55	60	22,20
25	3,85	62	23,69
26	4,17	65	26,00
27	4,49	70	30,20
28	4,83	75	34,70
29	5,14	80	39,50
30	5,55	85	44,55
32	6,31	90	49,94
33	6,71	95	55,64
34	7,06	100	61,55

TECHNICAL CHARACTERISTICS Caratteristiche tecniche

PRODUCT TYPE Drawn - *Trafilato* Ø 10÷80 mm
PRODOTTO Peeled - *Pelato* Ø 85÷100 mm

DIMENSIONAL TOLERANCE ISO h9
TOLLERANZE DIMENSIONALI

TECHNICAL CHARACTERISTICS Caratteristiche tecniche

PRODUCT TYPE Drawn - *Trafilato* Ø 3÷80 mm
PRODOTTO Peeled - *Pelato* Ø 20÷160 mm

