


PEELED ROUNDS
42CrMoS4V acc. to EN 10277-5
 Tondi pelati
 42CrMoS4V sec. EN 10277-5

diameter mm	weight kg/m	diameter mm	weight kg/m
20	2,47	46	12,93
21	2,72	48	14,20
22	2,98	50	15,40
23	3,26	52	16,70
24	3,55	55	18,70
25	3,85	56	19,30
26	4,17	58	20,70
27	4,49	60	22,20
28	4,83	62	23,69
29	5,14	65	26,00
30	5,55	70	30,20
32	6,31	75	34,70
33	6,71	85	44,55
34	7,06	90	49,94
35	7,55	95	55,64
36	7,99	100	61,55
38	8,90	80	39,50
40	9,86	85	44,55
42	10,91	90	49,94
44	11,83	95	55,64
45	12,50	100	61,55

TECHNICAL CHARACTERISTICS Caratteristiche tecniche

PRODUCT TYPE Peeled - Pelato Ø 20÷100 mm
PRODOTTO

DIMENSIONAL TOLERANCE ISO h9
TOLLERANZE DIMENSIONALI



GROUND ROUNDS
C45 acc. to EN 10277-2
 Tondi rettificati
 C45 sec. EN 10277-2

diameter mm	weight kg/m	diameter mm	weight kg/m
8	0,395	42	10,91
10	0,617	45	12,50
12	0,888	48	14,20
14	1,21	50	15,40
15	1,39	55	18,70
16	1,58	60	22,20
17	1,78	65	26,00
18	2,00	70	30,20
20	2,47	75	34,70
22	2,98	80	39,50
24	3,55	85	44,55
25	3,85	90	49,94
26	4,17	95	55,64
28	4,83	100	61,65
30	5,55	105	67,97
32	6,31	110	74,60
34	7,06	115	81,54
35	7,55	120	88,78
36	7,99		
38	8,90		
40	9,86		

TECHNICAL CHARACTERISTICS Caratteristiche tecniche

DIMENSIONAL TOLERANCE ISO h6, h7, h8
TOLLERANZE DIMENSIONALI



GROUND ROUNDS
42CrMoS4 acc. to EN 10277-5
 Tondi rettificati
 42CrMoS4 bonificato sec. EN 10277-5

diameter mm	weight kg/m	diameter mm	weight kg/m
20	2,47	45	12,50
25	3,85	50	15,40
30	5,55	60	22,20
35	7,55	70	30,20
40	9,86	80	39,50

TECHNICAL CHARACTERISTICS Caratteristiche tecniche

DIMENSIONAL TOLERANCE ISO h6, h7
TOLLERANZE DIMENSIONALI