



SQUARE DRAWN STEEL S355J2C acc. to EN 10277-2

Trafilati quadrati S355J2C sec. EN 10277-2

size mm	weight kg/m
20	3,14
25	4,91
30	7,06
35	9,62
40	12,60
45	15,90
50	19,60
60	28,30



SQUARE DRAWN STEEL S235JRC, C45 acc. to EN 10277-2

Trafilati quadrati S235JRC, C45 sec. EN 10277-2

size mm	weight kg/m
8	0,502
9	0,636
10	0,785
12	1,13
13	1,33
14	1,54
15	1,77
16	2,01
18	2,54
20	3,14
22	3,80
24	4,52
25	4,91
26	5,26
28	6,10
30	7,06
32	8,04
35	9,62
40	12,60
45	15,90
50	19,60
55	23,70
60	28,30
70	38,50
80	50,20
90	63,59
100	78,50



HEXAGONAL DRAWN STEEL S235JRC, C45 acc. to EN 10277-2

Trafilati esagonali S235JRC, C45 sec. EN 10277-2

size mm	weight kg/m
8	0,49
9	0,55
10	0,68
11	0,82
12	0,98
13	1,14
14	1,33
15	1,52
16	1,73
17	1,96
18	2,18
19	2,45
22	3,29
24	3,92
26	4,60
27	4,96
30	6,12

